

MOTOR ÝAGLARY SN/CF HIL DEREJELI

TŞ 05766698-29-2019



Görkezijiniň ady	Kysym üçin kada				
	Turkmenoil Advance 5W-30	Turkmenoil Advance 5W-40	Turkmenoil Advance 10W-40	Turkmenoil Advance 15W-40	Turkmenoil Advance 20W-50
Kinematiki süýgeşikligi 100°C-da, mm ² /s, çäklerde	9,3-12,5	12,5-16,3			16,3-21,9
Dinamiki süýgeşikligi CCS wiskozimetrinde, mPa·s, köp däl: - minus 30°C-da - minus 25°C-da - minus 20°C-da - minus 15°C-da	6600 - - -	- 7000 - -	- - 7000 -	- - -	- - 9500
Süýgeşiklik indeksi, az däl	140	130	120	110	
Aşgar sany, 1 g ýaga mg KOH, az däl	7,0				
	8,0				
Sulfat külüniň agramlaýyn paýy, %, köp däl	1,3				
Suwuň agramlaýyn paýy, %, köp däl	yzlary				
Mehaniki garyndylaryň agramlaýyn paýy, %, köp däl	0,015				
Açyk tigelde kesgitlenilýän ýalpyldama temperaturasy, °C, pes däl	200	205	210	220	
Doňma temperaturasy, °C, ýokary däl	minus 35	minus 30	minus 25	minus 20	
100°C-da M1 görnüşli mis plastinkasynda poslamasy, 3 sagatlap, ballar, köp däl	1B 1b				
Bugaryjylyk * 250°C-da 1 sagadyň dowamynda, %, köp däl	15				
Köpükleme meýilliligi/ köpügiň durnuklylygy, sm ³ , köp däl: 24°C-da 94°C-da 94°C-da synag edilenden soň 24°C- da	10/0 50/0 10/0				